

MD782

Digital Mobile Radio



- Superior Digital Voice with Analog Upgrade Option
- GPS Option and Integration with Data Applications





MD782

As a product built to the DMR standard, the MD782 delivers quality digital voice and data communications as well as all-round digital functions to increase your efficiency and enable you to be responsive to emergency situations. The radio can also be used as a control station to monitor and communicate with radio fleets from a desk. The MD782G is the GPS version of the radio, which allows integration with Hytera SmartDispatch or other 3rd party GPS Solutions.

Applications

Public Safety

Utilities

Security

Waste Management

Forestry

Construction

Logistics

Taxi



Product Features

- **User Friendly Design**
The large-size color display allows good visibility even under extremely strong light. The seven programmable keys facilitate your communication and the optional keypad microphone enhances.
- **Rugged & Reliable**
Complies with MIL-STD-810 C/D/E/F/G standards and is IP54 (5: Generally protected against dust; 4: Protected against the effects of light rain or minor water splashes) ensuring outstanding performance.
- **Higher Spectrum Efficiency, Higher Channel Capacity**
The TDMA technology allows twice the channels based on the same spectrum resource. This relieves the stress of increasing shortage in spectrum resource.
- **Secure Communication**
Besides the encryption inherent to digital technology, The MD782 provides enhanced encryption capabilities (such as 256-bit encryption algorithm). It has analog scrambling, and digital encryption using Advanced Encryption Standard (AES) and ARCFOUR (ARC4) encryption methodology to both voice and data.
- **Multifaceted Features**
In addition to conventional communication services, the MD782 is capable of Text Message, Scan, Emergency, Channel Steering, Auto Registration, Lone Worker, Radio Check, Remote Monitor, Call Alert, Radio Enable, and Radio Disable
- **Roaming**
Automatic roaming of all sites in an IP Multi-site Connect system.
- **Pseudo Trunk**
This virtual trunking feature allocates a free timeslot for urgent communications. This effectively enhances frequency efficiency and allows you to communicate in a timely manner in emergency situations.
- **Data Features**
Supports data capabilities of sending Private and Group text messages. It also supports a Third Party to control the radio via Third party API (GPS, Radio Registration Services, Radio Call Control, Telemetry, Data Transfer), via Telemetry control to radio.
- **Dual Mode: Analog & Digital**
Dual mode (analog & digital) operation ensures a smooth analog to digital migration.
- **Versatile Voice Calls**
The intelligent signaling of the MD782 supports various voice call types, including Private Call, Group Call , All Call and Emergency Call.
- **GPS Positioning**
Supports viewing of GPS positioning information and sending of GPS text message.
- **Expansion Ports**
This allows third parties to develop accessory and applications via front and rear port of the mobile. (Features such as channel steering, emergency footswitch can be supported via the rear port).
- **Various Analog Signaling Types**
Various analog signaling types (HDC1200, DTMF phone, 2-Tone, and 5-Tone), various squelch control types (CTCSS / CDCSS), thus providing higher function expansion capacity to the analog world.
- **One Touch Call/Text**
Supports One Touch features that comprise of Preprogrammed Text Messages, Voice Calls and Supplementary Features
- **Scan**
Capable of scanning of pure analog voice and signaling, pure Digital voice and data, and also mix mode scan that comprise of Analog and Digital activities.
- **Software Upgradeable**
Upgradeable software enables new features without buying a new radio; MD782(G) could also be switched into DMR trunking modes with corresponding trunking license applied in the same hardware.
- **Analog Upgradeable Version**
The Analog version of the MD782 can be upgraded at your organizations own pace to provide an easy step-by-step migration to digital technology. Analog features include 2-tone, HDC 1200, 5-tone Signaling, Scan, and Scrambler.

Accessories

Included

- Palm Microphone
- Microphone Hanger & Screws
- Mounting Bracket
- Power Cord
- Fuse
- GPS Antenna (MD782G only)

Optional



Keypad
Microphone
SM19A1



External
Speaker
SM09D1



Programming Cable
(USB Port)
PC37



Desktop
Microphone
SM10A1

Specifications

General	Frequency Range		VHF: 136 - 174MHz ; UHF1: 400 - 470MHz UHF2: 450 - 520MHz ; UHF3: 350 - 400MHz UHF5: 804 - 941MHz (only for DMR Trunking)	
	Channel Capacity		1024	
	Zone Capacity		64 (with a maximum of 16 channels each)	
	Channel Spacing		25 / 20 / 12.5KHz	
	Operating Voltage		13.6 V ± 15%	
	Current Drain		Standby	<0.6A
			Receive	<0.2A
			Transmit	5W: <5A 25W: <8A 45/50W <12A
	Frequency Stability		± 1.5ppm	
	Antenna Impedance		50 Ω	
	Dimensions (HxWxD)		2.36 x 6.85 x 7.87 inches	
	Weight		3.75 lbs	
	FCC ID	MD782	136-174 MHz: YAMMD78XVHF 400-470 MHz: YAMMD78XU1 450-520 MHz: YAMMD78XU2	
MD782G		136-174 MHz: YAMMD78XGVHF 400-470 MHz: YAMMD78XG-U1 450-520 MHz: YAMMD78XG-U2		
Industry Canada ID	MD782	138-174 MHz: 8913A-MD782VHF(L / H) 406.1-470 MHz: 8913A-MD782U1(L / H) 450-470 MHz: 8913A-MD782U2(L / H)		
	MD782G	138-174 MHz: Pending 406.1-470 MHz: Pending 450-470 MHz: Pending		

Environmental Specifications	Operating Temperature	-22° F ~ +140° F
	Storage Temperature	-40° F ~ +185° F
	ESD	IEC 61000 - 4 - 2 (level 4) ± 8kV(contact) ; ± 15kV (air)
	American Military Standard	MIL-STD-810 C/D/E/F/G
	Dust & Water Intrusion	IP54 Standard
	Humidity	Per MIL-STD-810 C/D/E/F/G Standard
	Shock & Vibration	Per MIL-STD-810 C/D/E/F/G Standard

GPS	TTFF (Time To First Fix) Cold Start	<1 minute
	TTFF (Time To First Fix) Hot Start	<10 seconds
	Horizontal Accuracy	<10 meters

Transmitter	RF Power Output	Low VHF & UHF1,2,3: 5-25W ; High VHF: 5-50W, UHF1,2,3: 5-45W UHF5: 5-35W
	FM Modulation (Analog Emissions Designator)	11K φF3E @ 12.5KHz; 14KφF3E @ 20KHz ; 16KφF3E @ 25KHz
	4FSK Digital Modulation (Digital Emissions Designator)	12.5KHz Data Only: 7K6φFXD 12.5KHz Data & Voice: 7K6φFXW
	Conducted/Radiated Emission	-36dBm<1GHz -30dBm>1GHz
	Modulation Limiting	± 2.5KHz @ 12.5KHz; ± 4.0KHz @ 20KHz ; ± 5.0KHz @ 25KHz
	FM Hum & Noise	40dB @ 12.5KHz; 43dB @ 20KHz ; 45dB @ 25KHz
	Adjacent Channel Power	60dB @ 12.5KHz 70dB @ 20/25KHz
	Audio Response	+1 ~ -3dB
	Audio Distortion	≤ 3%
	Digital Vocoder Type	AMBE++ or SELP
Digital Protocol	ETSI-TS102 361-1, 2&3	

Receiver	Sensitivity	Analog	0.3 μ V (12dB SINAD) ; 0.22 μ V (Typical) (12dB SINAD); 0.4 μ V (20dB SINAD)
		Digital	0.3 μ V/BER5%
	Selectivity TIA-603 ETSI	65dB @ 12.5KHz / 75dB @ 20/25KHz 60dB @ 12.5KHz / 70dB @ 20/25KHz	
	Intermodulation TIA-603 ETSI	75dB @ 12.5/20/25KHz 70dB @ 12.5/20/25KHz	
	Spurious Response Rejection TIA-603 ETSI	75dB @ 12.5/20/25KHz 70dB @ 12.5/20/25KHz	
	Blocking TIA-603 ETSI	90dB 84dB	
	S/N	40dB @ 12.5KHz; 43dB @ 20KHz ; 45dB @ 25KHz	
	Rated Audio Power Output	Internal	@20ohm load - 3W
		External	@8 ohm load - 7.5W
	Max Audio Power Output	Internal	@20ohm load - 8W
External		@8 ohm load - 20W	
Rated Audio Distortion	≤ 3%		
Audio Response	+1 ~ -3dB		
Conducted Spurious Emission	< -57dBm		

Your Local Dealer

Hytera reserves the right to change product designs or specifications at any time. If you have any questions regarding the accuracy of this information please contact your local sales representative or Hytera directly.

HYT, Hytera are registered trademarks of Hytera Co., Ltd. © 2013 Hytera Co., Ltd. All rights reserved.



Hytera America

Address: 3315 Commerce Parkway
Miramar, Florida 33025, USA
Tel: 800-845-1230 Fax: 954-846-1672
http://www.hytera.us
Stock Code: 002583.SZ

Hytera
Respond & Achieve