

EVX-530 SERIES

DIGITAL PORTABLE RADIOS

DMR Tier 2 Standard

Vertex Standard

eVerge™

SPECIFICATION SHEET

Evolve to Better Communication and Value

You can afford to enhance your communications with the digital performance of eVerge™ two-way radios. eVerge™ radios are compact and precision-engineered to deliver value without sacrificing quality — giving you more capabilities and the flexibility you need to communicate at your best.

Conversion Made Easy with Analog Integration

eVerge™ radios operate in both analog and digital modes and can be used with any existing analog two-way radios.

Do Digital Right: Stay Compatible and Maximize Efficiency

eVerge™ digital radios operate using the TDMA protocol for spectrum and power efficiency and lower total equipment cost compared to FDMA.

Better Radio Call Quality

Digital eliminates noise and static from voice transmit to only deliver the intended voice message crisply and clearly. eVerge™ digital radios feature the AMBE+2™ vocoder for enhanced voice quality.

Better Battery Life

Using eVerge™ radios in digital mode can operate up to 40% longer than typical analog mode as a result of the TDMA protocol and reduces overall battery consumption in transmit mode.

Better Message Control and Privacy

Control who you call and who gets your message in digital mode. Digital radios each have a unique ID enabling users to select who they need to call or send a text message without including others.

Better Coverage and Connection Monitoring with ARTS II™

Get ultra-clear audio right up to the edge of the transmit range. And, with Vertex Standard's exclusive Auto-Range Transpond System [ARTS II], you will always know when you are in or out of range with another ARTS II-equipped radio.

Submersible and Weatherproof

Meets international standard IP 57 for dust and water protection where fresh water does not harm the radio when submersed to 3 feet for up to 30 minutes.

Intrinsically Safe Option

Available as a future release: will meet SGS intrinsically safe requirements for use in hazardous situations.

Option Board Expandable for Additional Applications

The EVX-530 series is designed for future feature expansion and supporting third-party application development such as location tracking with GPS, telemetry, etc.




EVX-531

EVX-534

EVX-539

4.1" H x 2.3" W x 1.34" D



Option Board
Expandability



IP 57



SPECIFICATION SHEET

Additional Features

- ▶ 9 Programmable keys [EVX-539]
- ▶ 7 Programmable keys [EVX-534]
- ▶ 3 programmable keys [EVX-531]
- ▶ 8-Character alpha numeric display [EVX-534/539]
- ▶ Programmable tri-color LED custom call alert
- ▶ Voice compander
- ▶ Internal VOX
- ▶ RSSI Indicator [EVX-534/539]
- ▶ Voice inversion encryption [EVX-534/539]
- ▶ Lone worker alert
- ▶ Emergency alert
- ▶ Key lock
- ▶ Voice channel announce
- ▶ Priority scan
- ▶ Dual Watch scan
- ▶ Follow-me scan
- ▶ Nuisance channel delete
- ▶ Radio-to-radio cloning

Analog Mode Features

- ▶ Whisper mode
- ▶ CTCSS/DCS encode/decode
- ▶ MDC-1200® encode/decode
- ▶ 2-Tone encode/decode
- ▶ 5-Tone encode/decode
- ▶ DTMF Telephone Interconnect/ANI
- ▶ DTMF Paging [EVX-534/539]
- ▶ Remote stun/kill/revive [EVX-534/539]

Digital Mode Features

- ▶ Enhanced privacy [EVX-534/539]
- ▶ Text messaging
- ▶ All call, Group call, Individual call
- ▶ Escalart
- ▶ Remote monitor
- ▶ PTT ID encode [EVX-531]
- ▶ PTT ID encode/decode [EVX-534/539]
- ▶ Mixed mode scan
- ▶ One touch access [EVX-534/539]
- ▶ 128 Record contact list [EVX-534/539]

Accessories

- ▶ MH-37A4B: Earpiece microphone [RX/TX]
- ▶ MH-81A4B: Over-the-head light duty VOX headset
- ▶ MH-360S: Compact speaker microphone
- ▶ MH-450S: Speaker microphone
- ▶ MH-66A4B: IP 57 Submersible microphone
- ▶ FNB-V133LI-UNI: 1380 mAh Li-Ion battery
- ▶ FNB-V134LI-UNI: 2300 mAh Li-Ion battery
- ▶ VAC-UNI: Single-unit charger
- ▶ CLIP-20: Belt clip
- ▶ Leather cases available

EVX-530 Series Specifications

General Specifications		
Frequency Range	VHF: 136 - 174 MHz	UHF: 403 - 470 MHz 450 - 512 MHz
Number of Channels and Groups	32 / 2 [EVX-531]; 512 / 32 [EVX-534/539]	
Power Supply Voltage	7.5 V nominal	
Channel Spacing	25 * 20 * / 12.5 kHz	
Battery Life (5-5-90 duty w/battery saver)	VHF: FNB-V134LI-UNI: 2300 mAh Li-Ion 15.8 hrs [digital] / 12.0 hrs [analog] FNB-V133LI-UNI: 1380 mAh Li-Ion 9.7 hrs [digital] / 7.4 hrs. [analog]	UHF: 15.2 hrs [digital] / 11.5 hrs. [analog] 9.1 hrs [digital] / 7.0 hrs. [analog]
IP Rating	IP 57	
Operating Temperature Range	-22° F to +140° F [-30° C to +60° C]	
Dimension [H x W x D]	4.1 x 2.3 x 1.34 inches [106.7 x 58.5 x 34 mm] [w/FNB-V133LI-UNI]	
Weight [Approx.]	9.9 oz [280 g] w/FNB-V133LI-UNI, 11.5 oz [325 g] w/FNB-V134LI-UNI	
Receiver Specifications		
measured by TIA/EIA 603C		
Sensitivity:	Analog 12 db SINAD: 0.25 uV Digital 1% BER: 0.28 uV	
Adjacent Channel Selectivity	TIA603: 70/60 dB TIA603C: 70/45 dB	
Intermodulation	65 dB	
Spurious Rejection	70 dB	
Audio Output	500 mW @ 4 Ohms [INT] 350 mW @ 4 Ohms [EXT]	
Hum and Noise	40 dB	
Conducted Spurious Emission	-57 dBm	
Transmitter Specifications		
measured by TIA/EIA 603C		
Output Power	5.0/2.5/1.0/0.25W	
Modulation Limiting	16K0F3E / 11K0F3E	
Conducted Spurious Emission	70 dB below carrier	
Hum and Noise	40 dB	
Audio Distortion	<5% [3% typical]	
Frequency Stability	±1.5 ppm	
4FSK Digital Modulation	7K60F1D / 7K60F1E	
Digital Protocol	ETSI TS 102 361-1, -2, -3	

Applicable MIL-STD

Standard	Methods/Procedures				
	MIL 810C	MIL 810D	MIL 810E	MIL 810F	MIL 810G
Low Pressure	500.1/I	500.2/I,II	500.3/I,II	500.4/I, II	500.5/I, II
High Temperature	501.1/I,II	501.2/I, II	501.3/I, II	501.4/I, II	501.5/I, II
Low Temperature	502.1/I	502.2/I, II	502.3/I, II	502.4/I, II	502.5/I, II
Temperature Shock	503.1/I	503.2/I	503.3/I	503.4/I	-
Solar Radiation	505.1/I,II	505.2/II Cat. A1	505.3/II Cat. A1	505.4/I, II Cat. A1	-
Rain	506.1/I, II	506.2/I, II	506.3/I, II	506.4/I, III	506.5/I, II
Humidity	507.1/I,II	507.2/II, III	507.3/II, III	507.4/III	507.5/I, III
Salt Fog	509.1/I	509.2/I	509.3/I	509.4 / I	509.5/I
Dust	510.1/I	510.2/I	510.3/I	510.4/I, III	510.5/I
Vibration	514.2/VIII, X	514.3/Cat. 10	514.4/Cat. 10	514.5/ Cat. 20, 24	514.6/ Cat. 20, 24
Shock	516.2/I, III, V	516.3/I, IV	516.4/I, IV	516.5/I, IV	516.6/I, IV