

# VXR-1000

16 Channel 5 W  
VHF/UHF Vehicular Repeaters



Designed to enhance Public Safety and Industrial Communications Systems, the VXR-1000 Multi-Channel Cross-Band Vehicular Repeater provides dependable portable coverage throughout your system without the costly addition of site equipment. The VXR-1000 is a sophisticated, yet extremely simple to operate, addition to your mobile fleet to allow complete portable coverage utilizing the high output power of your mobiles. With a long list of built-in features, the VXR-1000 sets the standard for a cost effective way to optimize your system performance. Extremely small in size, and with a built-in DB-9 connector, the VXR-1000 will interface with most all brands of mobile radios in the market today. Let the VXR-1000 enhance your system now, and into the next century.



- Frequency Range:
  - VHF: 150~174 MHz
  - UHF: 450~470 MHz
- 16 Channel Capacity
- 5 Watts Power Output (Selectable 2.5, 1 and 0.5 W Low Power Levels)
- 12.5/25 kHz Bandwidth (Programmable By Channel)
- CTCSS/DCS Encode + Decode
- ARTS (Auto Range Transpond)
- Command Control (Allows VXR-1000 To Talk Directly With Portable)
- Built In Voice Inversion Encryption (Allows Secure Voice Between VXR-1000 and Portable)
- Local Volume Control (Requires External Speaker)
- First on Scene Logic With Priority Sampling
- Works With Most Popular Trunking Protocols
- Works With Most Low Band, VHF and UHF Systems
- PC Programmable
- MIL-STD 810 C/D/E





# VXR-1000

16 Channel 5 W  
VHF/UHF Vehicular Repeaters



## Specifications

General Specifications	VHF	UHF
Number of Channels	16 Channel	
Frequency Range	150-174 MHz	450-470 MHz
Crystal or Synthesized	Synthesized	
Channel Spacing	15 /30 kHz	12.5/25 kHz
Power Supply Voltage	13.8 VDC	
Ambient Temperature Range	-30°C to +60°C	
Frequency Stability	± 2.5 ppm	
RF Input-Output Impedance	50 ohms	
Audio Output Impedance	8 ohms	
Dimensions	1.0" (H) x 4.4" (W) x 5.4" (D) ( 25.4 x 111 x 136 mm)	
Weight	14.1 oz. (400 g)	

Receiver Specifications	Measurements made per EIA standard TIA/EIA-204D	
Circuit Type	Double Conversion Superheterodyne	
Sensitivity		
EIA 12 dB SINAD	0.30 µV	0.35 µV
20 dB Quieting	0.40 µV	0.45 µV
Threshold Squelch	0.25 µV to 2 uV	
Adjacent Channel Selectivity	60 dB	
Intermodulation	60 dB	
Spurious and Image Rejection	60 dB	
Conducted Spurious Emissions	-57 dBm	
Audio Response	+3/- 8 dB from the 6 dB/oct. De-emphasis curve	
Audio Output	1W into 8 ohms w/ <5% THD	
Hum and Noise	40 dB	

Transmitter Specifications	Measurement made per EIA standard TIA/EIA-152-C	
RF Power Output	5 / 2.5 / 1 / 0.5 W (HI/M2/M1/LO)	
Modulation	16K0F3E/11K0F3E	
Maximum Deviation	± 5 kHz / ± 2.5 kHz	
Conducted Spurious Emissions	60 dBc	
FM Hum and Noise	40 dB	
Audio Response	+1/- 3 dB from the 6 dB/oct. Pre-emphasis curve	
Audio Distortion	<5.0%	

Standard	MIL-810C Method/Procedures	MIL-810D Methods/Procedures	MIL-810E Methods/Procedures
Dust	510.1/Procedure 1	510.2/Procedure 1	510.3/Procedure 1
Vibration	514.2/Procedure 8,10	514.3/Procedure 1	514.4/Procedure 1
Shock	516.2/Procedure 1, 2, 3, 5	516.3/Procedure 1, 3, 4, 5, 6	516.4/Procedure 1, 3, 4, 5, 6

**The Vertex Warranty \***  
Vertex Radio Communications equipment includes an industry-leading 3- Year Limited Warranty on all transceivers and a 1-Year Warranty on all accessory items.  
\* U.S. and Canada

## Accessories & Options

- MLS-100 External Speaker (12 Watt)
- MH-25A8J Microphone
- VPL-1 Radio to Computer Programming Cable
- FRB-4 Alignment Interface Box
- T9101411 Cloning Cable (set to set clone)



MLS-100

MH-25A8J

VPL-1

T9101411

Communications Electronics  
2617 Palmer Road  
Hebron, Ohio  
740-929-2500

**YAESU U.S.A.**  
17210 Edwards Rd., Cerritos, CA 90703  
**YAESU U.S.A. INTERNATIONAL DIVISION**  
17210 Edwards Rd., Cerritos, CA 90703